

KBPC6/BR6 SERIES


**SINGLE PHASE 6.0 AMPS.
SILICON BRIDGE RECTIFIERS**

**Voltage Range
50 to 1000 VOLTS
Current
6.0 Amperes**

Features

- UL Recognized File # E-230084
- High surge current capability
- Low forward voltage drop
- High temperature soldering guaranteed:
250°C/10 seconds/.375" (9.5mm)
lead lengths at 5 lbs. (2.3kg) tension
- Small size, simple installation
- Leads solderable per MIL-STD-202,
Method 208

KBPC6/BR6



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%

Type Number		BR6005 KBPC6005	BR601 KBPC601	BR602 KBPC602	BR604 KBPC604	BR606 KBPC606	BR608 KBPC608	BR610 KBPC610	UNITS
Maximum Repetitive Peak Reverse Voltage	VRRM	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	VRMS	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	VDC	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current @TA = 50°C	IF(AV)	6.0							A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	IFSM	200							A
Maximum Instantaneous Forward Voltage Drop Per Leg @6.0A	VF	1.0							V
Maximun DC Reverse Current @ TA = 25°C at Rated DC Blocking Voltage @ TA = 100°C	IR	10 55							uA uA
Operating Temperature Range	TJ	-55 to +125							°C
Storage Temperature Range	TSTG	-55 to +150							°C



Diode



Capacitors

RATING AND CHARACTERISTIC CURVES KBPC6/BR6 SERIES

FIG.1- MAXIMUM NON-REPEETITIVE FORWARD SURGE CURRENT PER BRIDGE ELEMENT




FIG.2- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.3- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS PER BRIDGE ELEMENT




FIG.4- TYPICAL REVERSE CHARACTERISTICS PER BRIDGE ELEMENT

